

CODICE CODE	POTENZA POWER	FLUSSO APPARECCHIO FITTING OUTPUT	FLUSSO SORGENTE LIGHT SOURCE OUTPUT	TEMPERATURA TEMPERATURE	CRI	OTTICA BEAM
L00QS4060LI40010	10 W	979 lm	1450 lm	4000 K	≥80	60°
L00QS4060LI40020	20 W	1980 lm	2900 lm	4000 K	≥80	60°

NOTE:

- Disponibile su richiesta la versione 3000 K, 5000 K e 5700 K / 3000 K, 5000 K and 5700 K version available on request.
- Flusso luminoso 3000 K: -3%; flusso luminoso 5000 K e 5700 K: +3% / Luminous flux 3000 K: -3%; luminous flux 5000 K and 5700 K + 3%
- Decadimento del flusso luminoso ≤50.000 hr L85B15 / Decay of the luminous flux ≤50.000 hr L85B15



**Corpo**

Corpo in alluminio pressofuso in lega UNI EN 1706 (Basso tenore di Rame) verniciato a polvere poliestere. Dotato di staffa in ferro zincato verniciato. Viteria in acciaio inox AISI 304. Guarnizioni in silicone.

**Sorgenti**

Sorgente luminosa a LED con diverse possibilità di temperatura colore (standard Natural White 4000 K, esecuzione a richiesta anche con 3000 K, 5000 K e 5700 K).  
Alto coefficiente di resa cromatica CRI≥80. Ottiche in PC ottico. Ottica disponibile: simmetrica 60°.

**Alimentazione**

Integrata a bordo del PCB. Voltaggio 230V AC 50Hz. Temperatura d'esercizio -40° +45°.

**Applicazioni**

Decorazione facciate  
Vetrine  
Cartelloni pubblicitari

**Body**

Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanized iron bracket. Screws made of AISI 304 stainless steel. Silicone gaskets.

**Sources**

LED light source with different possibilities of color temperature (standard Natural White 4000 K and 3000 K, 5000 K and 5700 K available on request). High coefficient of chromatic performance CRI≥80. PC optical optics. Available optic: symmetrical 60°.


**Power Supply**

Integrated on PCB. Voltage 230V AC 50Hz. Operating temperature -40° + 45°.

**Applications**

Facades decoration  
Shop windows  
Big boards

Curve fotometriche / Photometric curves



Accessori / Accessories



Kit supporto picchetto  
fissaggio a terreno  
Ground spike  
support kit  
LKITA00000000022

Raccordo testa  
palo B  
Pole connection B  
LKITA00000040109

Connettore rapido  
IP 3 poli  
Fast connector  
IP 3 poles  
LKITA00000000003